

V200 SPEC

Model	PDA Rugged smartphone	Size: 165x78x23
ID		IP55 Weight: 296g 279g
Operation	Android 10.0	
CPU	MTK6761 Quad core	
Storage	ROM+RAM,16GB+2GB	Optional: 64GB+4GB
LCD	5.0" (IPS 720*1280)	
Camera	Rear 8.0MP	
GSM/3G/4G	GSM:B5/850;B8/900;B3/1800;B2/1900; 3G:WCDMA B1/2100;B2/1900;B5/850;B8/900; 3G:TD/SCDMA(Only support China Mobile) 4G: FDD-LTE,B1/2100;B3/1800;B7/2600;B20/800; 4G: TDD: B38/B39/B40/B41(Only support China Mobile)	
BT	BT4.0+EDR; Support SDAP, HSP, HFP, AVRCP, A2DP, OPP, PBAP。	
WiFi	Support 2.4/5GHz A/B/G/N/ AC dual band Wi-Fi	
Radio	Support	
Navigation	GPS, GLONASS	
Scanner	Honeywell N5703, zebra 4100, Newland CM30: Scan frame rate:: 60tims per second Scan distance: narmal light 584MM, dark light 100MM Scan type: Linear: UPC/EAN/JAN, GS1 DataBar, Code 39, Code 128, Code 32, Code 93, Codabar/NW7, Interleaved 2 of 5, Code 2 of 5, Matrix 2 of 5, MSI, Telepen, Trioptic, China Post 2D Stacked: PDF417, MicroPDF417, GS1 Composite 2D Matrix: Aztec Code, Data Matrix, QR Code, Micro QR Code, MaxiCode, Han Xin Code Postal: Intelligent Mail Barcode, Postal-4i, Australian Post, British Post, Canadian Post, Japanese Post, Netherlands (KIX) Post, Postnet, Planet Code OCR Option: OCR-A, OCR-B, E13B (MICR)	

Zebra 5500**Table 15** SE5500 Working Decode Ranges

Symbology	Typical Working Range (inches/centimeters) @ 20 Ft-Cd Minimum	
	Start	End
3 mil Code 39	2.7/6.9	16.2/41.1
5 mil Code 39	2.5/6.4	26.6/67.6
5 mil PDF417	2.8/7.1	19.6/49.9
6.67 mil PDF417	2.6/6.6	25.6/65.0
80% UPCA	2.0/5.0 *	55.5/141
100% UPCA	2.5/6.4 *	71/180
10 mil Data Matrix	2.2/5.6	27.1/68.8
15 mil Code 128 (4 in. wide)	7.2/18.2*	72/181
20 mil Code 39	*	109/277
55 mil Code 39	*	293/744
100 mil Code 39	*	554/1407

USB Port	TYPE-C	
SIM Card	Dual Nano sim card;	
T-flash	Max support 128GB	
Sensor	3D accelerator,E-compass,proximity sensor,Light sensor supported	
Battery	3900 mAh	
Backup battery	500 mAh	Optional
NFC	NXP NQ310 ,Support 14443A Topza, 14443A MIFARE UL, JIS 6319-4 Sony Felica, 14443A/B NXP DESFire	Optional
Video	3gp/H.265/MPEG4, H.265/MPEG-4/VP8/H.265	
Motor	Support	
Accessories	Adaptor,USB cabel,key,user manual,giftox	.
Extended port	RFID Extended port,	Optional
LF	134.2KHz FDX-B and HDX according to ISO/IEC11784/5	Optional
Weight	303g	